

tenGlobalMethods

DeviceOn(hs4, FeatureRef As Integer, Optional CheckFirst as Boolean = False, Optional UseControlLabel as Boolean = True) As String
DeviceOn(hs4, FeatureRefs As List(Of Integer), Optional CheckFirst as Boolean = False, Optional UseControlLabel as Boolean = True) As String
DeviceOn(hs4, Category As String, Optional CheckFirst as Boolean = False, Optional UseControlLabel as Boolean = True) As String
DeviceOn(hs4, Categories() As String, Optional CheckFirst as Boolean = False, Optional UseControlLabel as Boolean = True) As String

DeviceOff(hs4, FeatureRef As Integer, Optional CheckFirst as Boolean = False, Optional UseControlLabel as Boolean = True) As String
DeviceOff(hs4, FeatureRefs As List(Of Integer), Optional CheckFirst as Boolean = False, Optional UseControlLabel as Boolean = True) As String
DeviceOff(hs4, Category As String, Optional CheckFirst as Boolean = False, Optional UseControlLabel as Boolean = True) As String
DeviceOff(hs4, Categories() As String, Optional CheckFirst as Boolean = False, Optional UseControlLabel as Boolean = True) As String

DeviceDim(hs4, FeatureRef As Integer, Percent As Double) As String
DeviceDim(hs4, FeatureRefs As List(Of Integer), Percent As Double) As String
DeviceDim(hs4, Category As String, Percent As Double) As String
DeviceDim(hs4, Categories() As String, Percent As Double) As String

ToggleDevice(hs4 As HomeSeer.PluginSdk.IHsController, DevRef As Integer, Value1 As Double, Value2 As Double) As String
ToggleDeviceOnOff(hs4 As HomeSeer.PluginSdk.IHsController, DevRef As Integer) As String

IsOff(hs4, FeatureRef As Integer) As Boolean
AreAllOff(hs4, FeatureRefs As List(Of Integer)) As Boolean
AreAllOff(hs4, Category As String) As Boolean
AreAllOff(hs4, Categories() As String) As Boolean

tenGlobalMethods

SaveDeviceStates(hs4, SaveName As String, DevRefs As List(Of Integer)) As String

SaveDeviceStates(hs4, SaveName As String, Category As String) As String

SaveDeviceStates(hs4, SaveName As String, Categories() As String) As String

RestoreDeviceStates(hs4, SaveName As String, Optional Clear As Boolean = False) As String

RemoveDeviceStates(hs4, SaveName As String) As String

GetFeatureRefByFullName(**hs** As HomeSeerAPI.IHSApplication, DeviceName As String, FeatureName As String, Optional FeatureNameOnly As Boolean = False) As Integer

GetFullNameByRef(hs4 As HomeSeer.PluginSdk.IHsController, DevRef As Integer) As String()

GetCategoriesByRef(hs4 As HomeSeer.PluginSdk.IHsController, Devref As Integer) As List(Of String)

GetRefsByCategoryName(hs4 As HomeSeer.PluginSdk.IHsController, CatName As String) As List(Of Integer)

GetRefsInBothLists(List1 As List(Of Integer), List2 As List(Of Integer)) As List(Of Integer)

GetRefsInEitherList(List1 As List(Of Integer), List2 As List(Of Integer)) As List(Of Integer)